



Remaco PRO-L motorized projection screen is one of the most technically advanced screen today. It has revolutionized a typical screen design in terms of features and outlook. Unlike normal motorized screens, it is made of high quality screen fabric and designed for ease of operation, control and installation.

- ✓ Infrared Remote to control screen up/stop/down position
- ✓ Electronic Screen Control with wide angle sensor
- ✓ Direct connection to AV Control System
- ✓ More durable (Due to smooth roll up)
- ✓ Compact, Light weight and Beautiful Finishing
- ✓ Ease of installation
- ✓ Universal Mounting kit for all types mounting
- ✓ Adjustable setting for desired up/down position
- ✓ Adjustable screen position horizontally

Standard Screen Sizes

Model	Diagonal (Inches)	Width x Height
-------	-------------------	----------------

Standard Sizes (with 3 sides black borders)


PRO-L 3030	150"	120" x 120" (305 x 305 cm)
PRO-L 3636	180"	144" x 144" (366 x 366 cm)
PRO-L 3939	190"	154" x 154" (390 x 390 cm)
PRO-L 4040	200"	158" x 158" (400 x 400 cm)

Standard Sizes (with 4 sides black borders)

PRO-L 3023	150"	120" x 90" (312 x 237 cm)
PRO-L 4030	200"	157" x 118" (407 x 308 cm)



Electronic Screen Control (ESC)



Infrared Remote Control

Video Format (4:3), HDTV Format (16:9) and Nonstandard screen sizes are also available. Please consult your dealer for more information. All screens supplied are with black borders. Every screen is supplied with remote control, electronic screen control and universal brackets.

Specifications :

Motor Speed :	30 rpm
Operating :	120 deg. Celsius (thermostat cut off motor)
Fabric Roll Speed :	5.0 m/min (8.3 cm/sec)
Screen Gain :	1.2
Viewing Angle :	+/- 70 deg. (140 deg. viewing cone)
Screen Materials :	Matte White with fibreglass coating, Flame Retardant and fungus resistant
External Wired Control:	Normally open, momentary contact closure (voltage free)
IR Remote Sensitivity Distance :	Maximum 15 metres
Sensor Coverage :	160 deg. (horizontal) 150deg. (vertical)
Power Consumption :	195W (with load) 10W (without load)
Current :	1.8 or 0.85 Amperes
Voltage :	100 - 120 VAC or 220 - 240 VAC, 50/60 Hz



Screen with 3 sides black border



Video Format Screen with 4 sides black border

