

AV Accessories Series

Remaco AVA-280 & AVA-282 Active Speakers come with Wall / Ceiling bracket are specifically designed for custom installation applications with accurate reproduction, correct tonal balance and reliability. Speaker allows the user to direct high frequencies toward a desired listening area. High-quality, full range sound is then radiated from the entire surface. Possible applications include video conferencing, board rooms, home cinema screens, audio banners and many others.

AVA-280**Speaker Specifications:**

Woofer	: 5" Polypropylene
Tweeter	: 1" Dome
Power	: 35W
Frequency response	: 60Hz-18KHz
Sensitivity	: 89dB

Amplifier Specifications:

Power Output	: 30W
Frequency response	: 20Hz-20KHz
Equalization	: 2bands EQ ±15dB
Gain	: 30dB (max)
Voltage	: 230V AC/ 50Hz
Dimension (H x W x D)	: 240 x 180 x 175mm
Net weight (1 pair)	: 5.6kgs

AVA-282**Speaker Specifications:**

Woofer	: 6.5" Polypropylene
Tweeter	: 1" Dome
Power	: 50W
Frequency response	: 55Hz-20KHz
Sensitivity	: 89dB

Amplifier Specifications:

Power Output	: 50W
Frequency response	: 20Hz-20KHz
Equalization	: 2bands EQ ±15dB
Gain	: 30dB (max)
Voltage	: 230V AC/ 50Hz
Dimension (H x W x D)	: 285 x 205 x 180mm
Net weight (1 pair)	: 7.8kgs